



3 KERN KIB-TM

Practical Flip/Flop display device for greatest ease of use

4 KERN KXG-TM**

IP68 display device with integrated power supply

5 KERN KFT-TM**

KERN **easytouch** display device – the intuitive way to weigh

Note to see what options are offered by this display device, please see the KERN platform scale EOC on page 93

Note ideal, when you are looking for an affordable display device with the key industrial functions

Note to see what options are offered by this display device, please see the KERN platform scale IFT on page 102/103

STANDARD

CAL EXT, RS 232, KCP, GLP, PCS, SUM, PERCENT

STANDARD

TOL, MOVE, IP 65, MULTI, DMS, 1 DAY, ACCU

OPTION

IP 68, 230 V, 1 DAY

FACTORY

ALIBI, USB, BT 4.0, WLAN, SWITCH, LAN, M

STANDARD

CAL EXT, GLP, PCS, SUM, UNIT, TOL, MOVE

STANDARD

IP 68, 230 V, 1 DAY

OPTION

RS 232, RS 485, BT 2.0, WLAN, ACCU, M

STANDARD

CAL EXT, MEMORY, RS 232, USB, LAN, INTERN, PCS

STANDARD

RECIPE, PERCENT, UNIT, TOL, MOVE, MULTI, 1 DAY

OPTION

ACCU

FACTORY

BT 2.0, WLAN, M

Features	Model KERN 3 KIB-TM	Model KERN 4 KXG-TM**	Model KERN 5 KERN KFT-TM**
Display (segments)	7 digits	6 digits	6 digits
EC type approval	*on request	yes	-
Resolution verifiable	3000 e	10000 e	-
Resolution non verifiable	30000 d	30000 d	30.000 d
Weighing ranges	≤ 2	≤ 2	≤ 2
Weighing units	kg, g	kg, g	kg, g
Read-out	1, 2, 5, 10, n	1, 2, 5, 10, 20, 50	1, 2, 5
Piece counting with reference	5, 10, 20, 25, 50, 100	10, 20, 50, 100, 200	10, 20, 50, 100, 200
Display, digit height	Backlit LCD display, 24 mm	Backlit LCD display, 55 mm	Backlit Graphic LCD touch display, 12 mm
Additional functions	Totalising, HOLD function, printing of time. KCP Only possible through RS-232; USB, Bluetooth, WLAN, LAN on request	PRE-TARE function, totalising, HOLD function, peak hold, zero-point memorisation, printing of date and time	8 GB internal memory, 64 MB RAM, Dual-Core processor, password protection, user profiles
Strain gauge load cells	87-1100 Ω	87 - 1600 Ω	80 - 1200 Ω
Linearisation	3 points	2-7 points	2 points
Input voltage	12 V DC, 1000 mA	110-230 V AC	12 V DC, 2500mA
Permissible ambient temperature	-10 °C/40 °C	-10 °C/40 °C	-10 °C/40 °C
Interface RS-232	yes	KXS-A04	-
Interface RS-485	-	KXS-A01	-
Interface USB	KIB-A03, see page 93	-	yes
Interface Bluetooth	KIB-A04, see page 98	KXS-A02 (balance ► PC)	-
WLAN	KIB-A10, see page 93	YKI-03, see page 158	YKI-09, see page 102/103
SWITCH (DIGITAL I/O)	KIB-A09, see page 93	-	-
LAN	KIB-A02, see page 93	-	-
Foot switch	-	KXS-A03	-
Stand	EOC-A05, see page 93	YKP-02	-
Benchtop stand for display device/wall mount	EOC-A04	yes/yes	yes/yes
Protective working cover	EOC-A01S05	-	yes/yes
Rechargeable battery pack	KFB-A01, see page 93	GAB-A04	KFB-A01
Operating/charging time	up to 43 h/3 h	up to 80 h/12 h	up to 7 h/12 h
Dimensions Housing W×D×H	268×115×70 mm	232×170×80 mm	252×152×134 mm
Net weight	0,8 kg	2 kg	1 kg

** ONLY WHILE STOCKS LAST

KERN Pictograms

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	 Suspended weighing: Load support with hook on the underside of the balance
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required	 GLP/ISO log: With weight, date and time. Only with KERN printers	 Battery operation: Ready for battery operation. The battery type is specified for each device
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 Rechargeable battery pack: Rechargeable set
 Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Data interface RS-232: To connect the balance to a printer, PC or network	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition	 Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 USB data interface: To connect the balance to a printer, PC or other peripherals	 Totalising level A: The weights of similar items can be added together and the total can be printed out	 Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
 Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	 Percentage determination: Determining the deviation in % from the target value (100 %)	 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate
 WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals	 Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Weighing with tolerance range: (Check-weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 Interface for second balance: For direct connection of a second balance	 Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Verification possible: The time required for verification is specified in the pictogram +3 DAYS
 Network interface: For connecting the scale to an Ethernet network	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram +3 DAYS
 Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module	 Stainless steel: The balance is protected against corrosion	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram 1 DAY
 KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems		 Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram 2 DAYS

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer: